

No Skidding®



266 Wildcat Rd, Toronto, ON M3J 2N5 Canada
Phone: (416) 667-1788 Fax: (416) 667-1783
sales@noskidding.com www.noskidding.com
or call us Toll Free at 1-800-375-0571

We warehouse within the U.S. for our U.S. customers

TEXTURED ACRYLIC SLIP RESISTANT SPRAY #11935C - CLEAR

Description

No Skidding Slip Resistant Acrylic Clear Aerosol Spray, Product No. 11935C is a clear acrylic resin blend that air dries rapidly and retains translucency, durability, flexibility and non yellowing characteristics. 11935C is formulated using a recycled plastic particle for enhanced anti slip properties. This product is designed for increasing traction on steps, ramps, boat decks, diving boards, snowboards, skateboards, surfboards and other sport surfaces where increased traction is needed. Ideal for coating concrete, wood, and acrylic surfaces.

Surface Preparations

Surface must be clean dry and free of grease and other contaminants. Clean with No Skidding Flexclean or On Guard and sand surface if required. If cleaned with No Skidding Flexclean or On Guard then after cleaning be sure to rinse thoroughly and be sure that the surface has dried completely before applying coating.

Surface should be slightly abraded before application using 000 steel wool or other fine particle size media. As product wears further applications may be necessary. Coating should be steel wool abraded between coats.

Application

No Skidding Slip Resistant Acrylic Spray is designed for aerosol spray application. Clean overspray with acetone. **Always test small area before application. Read application instructions on label.**

Surfaces Suitability

Concrete, acrylic, wood, fiberglass.

Safety

This product contains solvents and/or other chemical ingredients. Adequate health and safety precautions should be observed during all storage, handling, use and drying periods.

READ MATERIAL SAFETY DATA SHEET BEFORE USING THIS PRODUCT.

Limitations

The technical data and suggestions for use in this product data sheet are currently correct to the best of our knowledge, but are subject to change without notice. Because application and conditions vary, and are beyond our control, we are not responsible for results obtained in using this product, even when used as suggested. The user should conduct tests to determine the suitability of the product for the intended use under then existing conditions. Any liability we may have with respect to a product or its use (including liability for breach of warranty, strict liability in tort, negligence or otherwise) is limited exclusively to replacement of the product or refund of its price. Under no circumstances are we liable for incidental and consequential damages.

PLEASE READ AND FULLY UNDERSTAND LABEL AND MSDS BEFORE USING.

Important: Seller's and manufacturers only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for the intended use, and the user assumes all risk and liability whatsoever in connection therewith. No statement of recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of the seller and manufacturer. Buyer assumes all risk and liability associated with disposal.

No Skidding® products are in use around the world in hotels, warehouses, factories, shopping malls, public transit systems, airports, hospitals and senior care, office complexes, restaurants, day care, schools, fitness clubs, government and military facilities.

The most complete range of slip injury prevention products in the World.



Physical Properties

Type	Slip resistant texture acrylic coating. Spray, product no. 11935C
Vehicle	Acrylic
Volume solids	11.7%
Weight solids	15.25%
Weight per spray	1 lb.
Viscosity	Thin liquid
Coverage	25 ft2 @ 1 mil
Recommended dry film	1.0 mil minimum
Gloss	Satin
Cleanup	Toluene, Xylene, or Lacquer thinner
% Paint per spray can	45%
Color	Clear
Dry Time	10-20 minutes at 77 degrees Fahrenheit
Full Cure	24 hrs @ 77 degrees Fahrenheit
Packaging	12 X 12 oz. net wt cans per case

No Skidding®



www.noskidding.com

266 Wildcat Rd, Toronto, ON M3J 2N5 Canada
Phone: (416) 667-1788 Fax: (416) 667-1783
sales@noskidding.com www.noskidding.com
or call us Toll Free at 1-800-375-0571

We warehouse within the U.S. for our U.S. customers

* No Skidding® is a registered trademark of No Skidding Products, Inc., Toronto Canada

E.&.O.E.