

No Skidding®



EPICOTE EPOXY

SLIP RESISTANT FLOOR COATING WITH INTEGRATED TRACTION

#79000 SERIES

266 Wildcat Rd, Toronto, ON M3J 2N5 Canada
Phone: (416) 667-1788 Fax: (416) 667-1783
sales@noskidding.com www.noskidding.com
or call us Toll Free at 1-800-375-0571

We warehouse within the U.S. for our U.S. customers



No Skidding® Slip Resistant Epoxy Floor Coating with Integrated Traction #79000 Series

Single part, with integrated silica type grit, provides a durable coarse non-slip surface. For interior use on wood, concrete, or steel surfaces that require safe footing. Resistant to gasoline, acids and most oils. Also resists hydraulic oils, grease, alcohol, etc.

Intended Uses

No Skidding® Slip Resistant Epoxy Floor Coating with Integrated Traction is designed to provide sure, safe footing on wet or sloped areas in manufacturing operations, warehousing facilities, indoor walkways, ramps, loading docks and anywhere a tough non-slip surface is required. Concrete must be at least 90 days old before using this product.

Typical Applications

Manufacturing operations, warehouses, walkways, ramps, loading docks etc.

Product Characteristics

- Helps prevent hazardous working conditions
- Simple application – ready to use, no messy measuring or mixing
- Durable – formulated with epoxy resin to stand up to wear and abuse
- Economical – just apply with low pile roller
- Versatile – use on concrete, wood or stone floors
- Beautifies – available in grey, green, red, yellow, black, beige and sand
- Clean up with mineral spirits

**READ DETAILED GENERAL INSTALLATION INSTRUCTIONS BEFORE
APPLYING PRODUCT. SEE MSDS FOR TECHNICAL DATA.**

Directions

Surface must be dry and free from dirt, rust, grease, oil and loose paint. For best results, smooth concrete surfaces should be etched with a 20% solution of muriatic acid. A phenolic core or low pile roller is recommended, no primer or thinner is necessary.





Approximate Coverage

Single coat application approximately 100 sq.ft. per gallon.

Two coat application, approximately 150 sq.ft. per gallon when applied in thin coats. Second coat must be applied within 24 hours of first application for best adhesion.

TECHNICAL DATA

Weight Per Gallon	12.5 pounds	
Flash Point	105°F	
Coverage	150 sq.ft. per gallon	
Dry Time, To Touch	3 hours	
Dry Time, Hard	6-8 hours	
Dry Time, Between Coats	5-6 hours	
Dry Time, Open to Traffic	12-24 hours	
Available Colors:	Gray #79015	Black #79021
	Green #79017	Beige #79022
	Red #79019	Sand #79023
	Safety Yellow #79020	

** Available in 5 and 1 Gallon containers.

DURING APPLICATION, EXTINGUISH ALL FLAMES, INCLUDING PILOT LIGHTS, AND HAVE ADEQUATE VENTILATION. DO NOT USE IN CLOSED AREA.

PLEASE READ AND FULLY UNDERSTAND LABEL AND MSDS BEFORE USING.

Important: Seller's and manufacturers only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for the intended use, and the user assumes all risk and liability whatsoever in connection therewith. No statement of recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of the seller and manufacturer. Buyer assumes all risk and liability associated with disposal.

No Skidding® products are in use around the world in hotels, warehouses, factories, shopping malls, public transit systems, airports, hospitals and senior care, office complexes, restaurants, day care, schools, fitness clubs, government and military facilities.

The most complete range of slip injury prevention products in the World.



No Skidding® 
www.noskidding.com

266 Wildcat Rd, Toronto, ON M3J 2N5 Canada
 Phone: (416) 667-1788 Fax: (416) 667-1783
 sales@noskidding.com www.noskidding.com
 or call us Toll Free at 1-800-375-0571

We warehouse within the U.S. for our U.S. customers

* No Skidding® is a registered trademark of No Skidding Products, Inc., Toronto Canada

E.&O.E.