

No Skidding®



EPICOTE EPOXY

76000 SERIES, 79140 CLEAR & 79023 CLEAR SLIP RESISTANT

AVAILABLE IN LOW, MEDIUM & COARSE PROFILE

266 Wildcat Rd, Toronto, ON M3J 2N5 Canada
Phone: (416) 667-1788 Fax: (416) 667-1783
sales@noskidding.com www.noskidding.com
or call us Toll Free at 1-800-375-0571

We warehouse within the U.S. for our U.S. customers



Epicote Non Catalyzed Epoxy, Slip Resistant, Low Profile

Epicote provides the tough durability of Epoxy Ester resin with the convenience and simplicity of one component application. This product has outstanding resistance to rubber burns and scuffmarks, as well as many chemicals and oil spills. A one-component, gloss coating modified with epoxy ester for enhanced chemical resistance. Resists many chemicals including oil, grease, alcohol, mild solvents, cleaners, weak acids and alkalis. Dries to a tough film that resists wear from foot or forklift traffic. Recommended for factories, warehouses, service stations and other uses.

Recommended Uses

This product is an excellent concrete floor seal and finish, formulated to stand up to the constant wear and abuse that an industrial floor receives. Provides a durable, anti-slip finish for floors in stores, schools and office buildings. Also for wood floors.

AGRI-FOODS CANADA & U.S.D.A. AUTHORIZED FOR USE IN FEDERALLY INSPECTED MEAT AND POULTRY PLANTS.

Specifications (Products No. 79140 and 79023)

Resistant to skinning.....	Resistant
Flash point (TCC)	107°F
Tack free after 24 hours	Tack free
Not tacky after 15 minutes dry	Not tacky
No loss in dry after 7 days at 125°f	No loss
Little penetration: good sheen.....	Satisfactory
Damage – free: good adhesion between coats	Adhesion
Uniform appearance when patched	Uniform
Resistant to 50% alcohol	Resistant
Resistant to naptha	Resistant
Weight per gallon	7.2 pounds
Clarity, Clear Coat	clear & sharp

This coating is slip resistant when used with fine, medium or coarse traction beads.

Product Characteristics

Provides a tough seal and finish that is resistant to abrasion, impact scuffmarks, rubber burns, ink, fruit juices, soda, alcohol and water.

Clear Coat dries to an excellent gloss that will not cloud, nor yellow with age.

Highly recommended for wooden floors.

Simple application – comes ready to use. Available in slip-resistant and also smooth finish.

Exceptional levelling characteristics prevent formation of bubbles and lap marks, for professional finish every time.

Durable-Formulated to stand up to constant wear and abrasion.



Colors (Please specify fine, medium, or coarse traction)

Regular	Slip Resistant
79140 Clear	79023T Clear
76000 White	76000T White
76001 Grey	76001T Grey
76002 Green	76002T Green
76003 Red	76003T Red
76004 Dark Grey	76004T Dark Grey
76006 Beige	76006T Beige
76008 Yellow	76008T Yellow
76012 Black	76012T Black
76023 Sand	76023T Sand

Dry Time

Between coats8 hours
 To walk on24 hours

Surface Preparation

Curing seals and other sealers must be removed before application of this product. Do not apply to concrete that is less than 90 days old. Clean surface thoroughly, using heavy-duty cleaners and degreasers. All oil, grease dirt, loose paint, etc., should be completely removed before application of this product. If the concrete surface is smooth, an acid etch should follow the cleaning. The surface should then be thoroughly rinsed and allowed to dry overnight or until it is thoroughly dry.

Application Directions

Apply with low pile applicator. Two coats may be required. Apply second coat after first coat is dry and before 24 hours. Allow the surface to dry for 24 hours before putting surface to use. During application, extinguish all flames, including pilot light and have adequate ventilation. Do not use in closed areas. When recoating, screen back surface to remove gloss. This will insure bonding of the new coat to the old. To remove this product, use a paint remover.

PLEASE READ AND FULLY UNDERSTAND LABEL AND MSDS BEFORE USING.

Important: Seller's and manufacturers only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for the intended use, and the user assumes all risk and liability whatsoever in connection therewith. No statement of recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of the seller and manufacturer. Buyer assumes all risk and liability associated with disposal.

No Skidding® products are in use around the world in hotels, warehouses, factories, shopping malls, public transit systems, airports, hospitals and senior care, office complexes, restaurants, day care, schools, fitness clubs, government and military facilities.

The most complete range of slip injury prevention products in the World.

TECHNICAL DATA

(Based on Light Gray #76001)

Percent solids, in colors	40%
Color, gardner color standard	14 – 15
Clear Coat	
60° Gloss	85%+
Viscosity	65-75 KU
Flash point t.c.c.	over 100 fahrenheit
Set to touch - average	3 hours
Resistance to water (24 hours)	excellent
Approximate Coverage	350 sq. ft. per gallon

Packing

Available in 5 gallon and 1 gallon containers

* Clean up with mineral spirits

Read application instructions and MSDS before applying product.

No Skidding®



www.noskidding.com

266 Wildcat Rd, Toronto, ON M3J 2N5 Canada
 Phone: (416) 667-1788 Fax: (416) 667-1783
 sales@noskidding.com www.noskidding.com
 or call us Toll Free at 1-800-375-0571

We warehouse within the U.S. for our U.S. customers

* No Skidding® is a registered trademark of No Skidding Products, Inc., Toronto Canada

E.&O.E.