

# No Skidding®

266 Wildcat Rd, Toronto, ON M3J 2N5 Canada  
Phone: (416) 667-1788 Fax: (416) 667-1783  
sales@noskidding.com www.noskidding.com  
or call us Toll Free at 1-800-375-0571

We warehouse within the U.S. for our U.S. customers



# NSP No Skidding®

## SUPER ACRYLIC

### SLIP RESISTANT WITH INTEGRATED TRACTION

WATER BASED

## Product Description

- A tough, one part, anti slip coating suitable for a variety of interior and exterior applications.
- No Skidding Super Acrylic Slip Resistant with Integrated Traction also resists weathering, abrasion and mild chemicals.
- Significantly reduces the chances of slipping, although this product cannot totally prevent the possibility of slipping.
- Low odour and low VOC.
- Soap & water cleanup.

## Recommended Uses

- Suitable for use on walkways, steps, ramps, locker room floors, boat docks, around pools, steps, ramps, tennis courts and a variety of other interior and exterior concrete, wood and metal surfaces that have been properly prepared.

**Finish:** Textured Flat **Vehicle:** Acrylic Resin **Formulation:** Lead, Chromate and Mercury free

## Physical Data

**Gloss Rating:** Flat

**Percent Solids:** Weight: 63.9±2.0%, Volume: 45.7±2.0%

**VOC Category:** 2.1 lbs/gal (250 grams/litre)

**Viscosity:** 125-130 K.U.

**Net Wt. Per Gal:** 12.6±0.25 lbs/gal

**Flash Point:** 158°F Closed Cup

## Surface Preparation & Application Instructions

- All surfaces must be clean and free of dust, dirt, grease, mildew, soap residue, loose paint, glue size and any other foreign matter. For best results, the cause of any previous paint failure should be corrected before repainting.
- Floor is dry to walk on after 24 hours under good drying conditions.
- Pressure Treated Wood: Power wash thoroughly to remove oils in the wood before application.
- Apply with Low Pile Roller.

## Recommended Primers

**Metal:** Anti Rust Metal Primers **Galvanizing:** Galvanized Metal Primer

**Masonry / Wood / Concrete & Weathered Asphalt:** No primer required

## Application Temperature

**Minimum:** 50°F **Maximum:** 90°F

## Drying Time (Good Conditions)

**Tack Free:** 2 Hours **To Recoat:** 24 Hours

**Hard:** 7 Days



## Practical Coverage

100-125 sq. ft./gal. (Depending upon the porosity of the substrate)

## Dilution


Not normally recommended. If necessary, use small amounts of clean water.

## Recommended Film Thickness Per Coat

**Wet:** 12.8-16.0 mils **Dry:** 5.0-8.0 mils

\*Clean up with soap and water

## Colors Available



Gray 97301



Tile Red 97302



Black 97303



Brown 97304



Beige 97305



Handicap Blue



Yellow 97308



Tintable White 97309



Green 97313

PLEASE READ AND FULLY UNDERSTAND LABEL AND MSDS BEFORE USING.

**Important:** Seller's and manufacturers only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for the intended use, and the user assumes all risk and liability whatsoever in connection therewith. No statement of recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of the seller and manufacturer. Buyer assumes all risk and liability associated with disposal.

No Skidding products are in use around the world in hotels, warehouses, factories, shopping malls, public transit systems, airports, hospitals and senior care, office complexes, restaurants, day care, schools, fitness clubs, government and military facilities.

The most complete range of slip injury prevention products in the World.

# No Skidding®

www.noskidding.com

266 Wildcat Rd, Toronto, ON M3J 2N5 Canada  
Phone: (416) 667-1788 Fax: (416) 667-1783  
sales@noskidding.com www.noskidding.com  
or call us Toll Free at 1-800-375-0571

We warehouse within the U.S. for our U.S. customers

\* No Skidding® is a registered trademark of No Skidding Products, Inc., Toronto Canada

E.&.O.E.