

No Skidding®



TEXTURED EPOXY SLIP RESISTANT 79QD SERIES

266 Wildcat Rd, Toronto, ON M3J 2N5 Canada
Phone: (416) 667-1788 Fax: (416) 667-1783
sales@noskidding.com www.noskidding.com
or call us Toll Free at 1-800-375-0571

We warehouse within the U.S. for our U.S. customers

Characteristics

A one part epoxy coating specifically designed to give a hard textured coating for foot traffic on steel, fiberglass, treated aluminum, concrete, and properly primed wood substrate. Ideal for the boat, trailer, laundry room, bathroom, on steps, ramps and a variety of industrial and residential applications.



Surface Preparation

Surface should be dry, clean and free from contaminants such as oil, wax, dirt or mill scale. Aluminum surfaces should be treated first with an aluminum pretreatment before applying the coating. For concrete, clean with Flexclean or trisodium phosphate (TSP) and a firm bristle brush. Rinse thoroughly before paint application.

Application

May be applied by brush or roller. Dries to touch in 10-20 minutes. Dry hard in 24 hours or more depending on weather conditions. Do not subject to foot traffic in less than 24 hours on drying time. This product is not recommended for garage floors.

Physical Properties

Theoretical Coverage...200 ft² @3 mil dry film thickness
Drying time @ 77° (25°C), 50% Relative Humidity
Temperature and condition dependent
Touch.....10-20 minutes
Hard.....24 hours
Resin Type.....Epoxy Ester
Viscosity60-65 KU
Lb/gal.....9-10 #/g
Solid Weight50-55%
Coverage400sq. ft. per gal @ mil DFT

ASTM D4518-91

Measuring static fraction of coating surfaces:

- Steel -162
- Rubber -745

Curing

Where needed a non-lifting solvent base primer may be applied for added corrosion resistance.

Cleanup

Thinner, Toluene, Xylene, or Lacquer

Product Code	Product Colour
79QDG	Gray
79QDC	Clear
79QDW	White

Safety

This product contains solvents and/or other chemical ingredients. Adequate health and safety precautions should be observed during all storage, handling, use and drying periods.

See MSDS and label for precautionary and health hazard information.



PLEASE READ AND FULLY UNDERSTAND LABEL AND MSDS BEFORE USING.

Limitations: The technical data and suggestions for use in this product data sheet are currently correct to the best of our knowledge, but are subject to change without notice. Because application and conditions vary, and are beyond our control, we are not responsible for results obtained in using this product, even when used as suggested. The user should conduct tests to determine the suitability of the product for the intended use under then existing conditions. Any liability we may have with respect to product or its use (including liability for breach of warranty, strict liability in tort, negligence or otherwise) is limited exclusively to replacement of the product or refund of its price. Under no circumstances are we liable for incidental and consequential damages.

No Skidding® products are in use around the world in hotels, warehouses, factories, shopping malls, public transit systems, airports, hospitals and senior care, office complexes, restaurants, day care, schools, fitness clubs, government and military facilities.

The most complete range of slip injury prevention products in the World.

No Skidding®



www.noskidding.com

266 Wildcat Rd, Toronto, ON M3J 2N5 Canada
Phone: (416) 667-1788 Fax: (416) 667-1783
sales@noskidding.com www.noskidding.com
or call us Toll Free at 1-800-375-0571

We warehouse within the U.S. for our U.S. customers

* No Skidding® is a registered trademark of No Skidding Products, Inc., Toronto Canada

E.&O.E.