

No Skidding®



TEXTURED EPOXY

SLIP RESISTANT SPRAY #11930 SERIES

266 Wildcat Rd, Toronto, ON M3J 2N5 Canada
Phone: (416) 667-1788 Fax: (416) 667-1783
sales@noskidding.com www.noskidding.com
or call us Toll Free at 1-800-375-0571

We warehouse within the U.S. for our U.S. customers

Description

A slip resistant epoxy coating that cures to a tough, textured finish. Designed for exterior and interior use on concrete, steel, wood, fiberglass, aluminum, tile, etc. Particularly effective anywhere water or other slippery conditions exist. Contains synthetic grit with no sharp edges.

Advantages

- Slip Resistant
- Adheres to most hard surfaces
- A cost effective method of coating small areas
- Easy to apply, sets up quickly
- Contains Durable Microgrit



Intended Uses

No Skidding® Slip Resistant textured epoxy spray can be used to render the following surfaces slip resistant: steps, ramps, public restrooms, loading docks, around equipment running boards, step pads, ladders, boats, pool decks, diving boards, fire escapes.

Typical Application

Apartment buildings, hospitals, nursing homes, industrial plants, marinas, schools, municipalities, public institutions, office buildings, warehouses.

Colors

Clear (11930C), Gray (11930G), Safety Yellow (11930Y), Black (11930B) or White (11930W).

Surface Preparation

Surface must be clean, dry, and free of grease. Remove grease by washing with No Skidding® On Guard or suitable cleaner.

PLEASE READ DETAILED GENERAL INSTALLATION INSTRUCTIONS BEFORE APPLYING NO SKIDDING® SLIP RESISTANT TEXTURED EPOXY COATING.

Important: Seller's and manufacturers only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for the intended use, and the user assumes all risk and liability whatsoever in connection therewith. No statement of recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of the seller and manufacturer. Buyer assumes all risk and liability associated with disposal.

No Skidding® products are in use around the world in hotels, warehouses, factories, shopping malls, public transit systems, airports, hospitals and senior care, office complexes, restaurants, day care, schools, fitness clubs, government and military facilities.

The most complete range of slip injury prevention products in the World.

Product Specifications

Type	Slip resistant textured epoxy coating, Spray, product #11930 Series
Coverage	Approximately 25 sq.ft. per spray can
Appearance / Odor	Viscous liquid / Strong solvent odor
Flash Point of Concentrate	45°F
Aerosol Flammability	Extremely Flammable Spray
Specific Gravity of Concentrate	0.800
Propellant	Liquefied Petroleum Gas
Spray Pattern	Circular Coarse Fan spray
NFPA Fire Rating	Level 3 Aerosol
Packaging	12 X 12 oz. Net Wt. Cans per case (16oz. Size Cans)

See MSDS and label for precautionary and health hazard information.



No Skidding®

www.noskidding.com



266 Wildcat Rd, Toronto, ON M3J 2N5 Canada
Phone: (416) 667-1788 Fax: (416) 667-1783
sales@noskidding.com www.noskidding.com
or call us Toll Free at 1-800-375-0571

We warehouse within the U.S. for our U.S. customers

* No Skidding® is a registered trademark of No Skidding Products, Inc., Toronto Canada

E.&O.E.